



Polopropichovací svorka

SL9.11

Kód	SL9.11
GTIN	6418677403804
Název	Polopropichovací svorka AL 16-120 mm ² and Al 16-35 mm ²
Popis	SL9.11 is used for aluminium to aluminium connections. The connector has one bolt.
Dodavatel	Ensto Finland Oy

Technické parametry

Dimensions

Branch conductor mm ² :	Al 16-35
Main conductor mm ² :	Al 16-120
Net Weight:	0,1167 kg

Certificates

Standardy:	SFS 2663
------------	----------

Mechanical

Utahovací moment:	20 Nm
-------------------	-------

Others

ETIM Class:	EC001062
-------------	----------

ETIM Technické parametry

etim

Nominal cross section main conductor SM:	16 ... 120 mm ²
Nominal cross section branch conductor SE/RE:	16 ... 35 mm ²
Nominal cross section branch conductor SM/RM:	16 ... 35 mm ²
Material main conductor:	Aluminium
Material branch conductor:	Aluminium
Terminal insulated:	Yes

Clamping channel opening main conductor: Closed

Clamping channel opening branch
conductor: Closed

Surface protection: Bare

Type of connection: Insulation piercing connector IPC

Packaging

Carton (Default package)

Package size: 50 pce
Depth: 400 mm
Width: 265 mm
Height: 220 mm
Weight: 6,335 kg
Volume: 23,32 l

Pallet package

Package size: 1800 pce
Depth: 1200 mm
Width: 800 mm
Height: 1020 mm
Weight: 248,06 kg
Volume: 979,2 l